

**The installation guide and specifications are under.
GUIDE SPECIFICATIONS FOR DEXUNE**

METALWORKS BAFFLE CEILING SYSTEM with 100mm X 30mm in WOOD GRAIN FINISH

Providing & fixing Dexune Ceiling Vertical Linear Baffle Ceiling made out of G.I metal. The baffle blade shall be in size of 100x 30 x 2440mm in Wood grain finish. The baffle blade shall be suspended using Slotted U-profile at on-centre spacing in multiples of 150mm. longer lengths of Baffle to be connected by Baffle Joiner and the ends to be fixed with End caps.

Installation of –U Grid:

The U-profile to be suspended at every 1200mm on-centre using 6mm threaded rod from the structural soffit using U-profile hanger. U-profile splice to be used to join more than one U profiles of length 2440MM with flanges 20MM and 20MM Height & 35MM Width.

Installation of Dexune Ceiling Baffles:

Locate the slot for Baffle Hangers in slot of Baffle section at 1200mm centres. Hangers are inserted into the slot, then rotated 90° and fixed into position by tightening the grub screw. Each Hanger to be secured into position by inserting the Locking Clip.

Baffles blades to be connected at ends with Baffle Joiner, which are inserted into the top and bottom slots of the Baffle closed profile for alignment only. The bottom Joiner to be located first and fastened on one side only. The top Joiner to be fitted then and secured with grub screws on one side. Then the two Baffle sections shall be joined and the top Joiner is screw fastened on the 2nd Baffle profile.

End Caps to be located by pushing the End Cap tongues into Baffle slots.

Installation to be carried out by Dexune Ceiling Trained Installation team & Installation should be carried out as per Dexune Ceiling recommended procedure.

