



Description: - Rigitone Activ'Air 8/18



**Characteristics:**

Rigitone Activ'Air 8/18 comprises a 12.5mm gypsum core, with a regular round perforation of 8mm diameter. It is a specially formulated Gypsum board with Activ'Air technology.

**Physical Properties:**

- Board Dimensions : (1188x1998) mm
- Board Thickness : 12.5mm
- Board Weight : Approx. 9.5 Kg/m<sup>2</sup>
- Perforation Size : 8mm diameter
- Perforation Spacing : 18mm CTC
- Perforation Area : 15.5%
- Edge type : All 4 Square Edges
- Colour : Unpainted paper liner (can be painted with an emulsion paint after installation)

**NRC:**

Sr. No.	System ( Test Combination)	NRC
1	Rigitone Activ'Air 8/18 board +50mm air Gap	0.60
2	Rigitone Activ'Air 8/18 board +200mm air Gap	0.65

ORIGINAL


Made by :- Sunilkumar Yadav 

Approved by:- Shailendra Shinde 

1. Rigitone Activ'Air 8/18 board +50mm air Gap

Freq. (Hz)	125	250	500	1000	2000	4000
ABS Coeff.	0.15	0.30	0.65	0.85	0.60	0.45


NRC = 0.60



2. Rigitone Activ'Air 8/18 board +200mm air Gap

Freq. (Hz)	125	250	500	1000	2000	4000
ABS Coeff.	0.40	0.60	0.80	0.60	0.50	0.50

NRC = 0.65



**ORIGINAL**